



## FLEX CONNECTOR SELECTION DATA

<b>Project:</b>	
<b>Company:</b>	<b>Contact:</b>
<b>Phone:</b>	<b>Email:</b>

**Type of Flex Connector Required:**    Inlet     Outlet

<b>Size (H x W or Diameter):</b>	
<b>Flow Rate (CFM):</b>	
<b>Operating Pressure ("WG):</b>	
<b>Operating Temperature (° F):</b>	

**Flex Design Options:**

Standard:                       Standard with liner (Typical for inlet):                       Acoustic:

**Flange Material:**

HRS:                                       304 SS:                                       316 SS:

**Flex Material:**

EPDM with nylon insert (275° F):                                       Silicone impregnated fiberglass cloth (500° F):

**Flex Length:**

8" (Standard):                       10":                       12":                       Custom Length: Please call # below!

**Coatings:**

Standard primer (200° F):                                       International 2 coat system- Enamel (200° F):   
Carbozinc 11 inorganic zinc (750° F):                                       Interzinc 22 inorganic zinc epoxy (1000° F):

<b><u>Project Notes:</u></b>
------------------------------

Please print, complete, and scan form back to [info@systechdesign.com](mailto:info@systechdesign.com)

For any other questions, please contact 800-456-9460 to speak with a technical sales representative.

Thank you!